

SMAC

Moving Coil Actuators

PRODUCT CATALOG

AVS



www.smac-mca.com

The ability to do work and verify its accuracy at the same time.



SMAC Corporate Headquarters and Factory

About SMAC


SMAC was founded in 1990 in Carlsbad, California, USA with the target of developing devices that would automate work done by hands and fingers. By combining this capability with competitive prices SMAC believes it can eventually replace older technologies such as pneumatic cylinders and electric ball screw actuators.

SMAC now manufactures a wide range of precision programmable electric actuators based on its patented moving coil technology. These proprietary moving coil linear motor based designs are technically far ahead of old generation pneumatic and other electric actuators, including moving magnet linear motors. Our technological edge, combined with continuous cost-down/quality-up processes and its worldwide sales basis makes SMAC a leading mechatronics manufacturer in the world today.

SMAC devices have the ability to find surfaces without disturbing them, i.e., "Soft-Land™ capability." This makes them "Mechatronic Actuators."

SMAC Moving Coil Actuators are much more sophisticated than the simple devices such as solenoids or air cylinders. The variables involved in the work are programmable. So force, distance, and speed all can be varied as needed. The devices also have built-in feedback sensing that can report if the desired work was accomplished or not. The devices have the ability to find surfaces without disturbing them, i.e., "Soft-Land™ capability." This makes them "Mechatronic Actuators."

SMAC determined early in its development that there were key technologies it must control to be successful. These include designing and manufacturing high torque brushless DC motors and optical encoders. In 2008, SMAC began an in-house capability to design and produce incremental linear optical encoders. That effort led to the establishment of SMAC Electronics Manufacturing Center in New Hampshire. The group includes engineers and technicians with more than 35 years of experience designing and building encoder products.



LCA series Linear Actuators



Encoders




High Torque Brushless DC Motors

SMAC Moving Coil Actuators

How Moving Coil Actuators Work

Moving coil actuators work on the same principle as an audio loudspeaker. They consist of a moving carriage with an attached coil surrounding a powerful, permanent magnet. Current passing through the coil induces an electro-magnetic force, according to Fleming's left-hand rule. Varying the direction and amplitude of the current varies the induced force, allowing you to control the motion. The result is a device with few moving parts, low friction and zero backlash with excellent dynamic properties.



$$F \propto N I B$$

where: **F** is the force generated

N is the number of turns in the winding (Constant)

I is the current flowing through the winding and

B is the magnetic flux (Constant)

Therefore, doubling **I (current)** doubles **F (Force)**.

Other voice coil actuators give no provision for position feedback, but all SMAC actuators include a precision, non-contact linear encoder. This allows closed-loop servo control of motion in position and velocity modes and real time monitoring of position in all operating modes.

These unique features allowed SMAC to develop the Soft-Land™ routine, which has permitted applications simply not possible with other technologies.

Benefits of Moving Coil Technology

- Lower moving mass with the moving coil actuator means extremely high acceleration and velocity, as opposed to the heavier "moving magnet" technology used in most linear motors.
- Safe and energy efficient: operates at low current, typically at 1.5 amps at 24 volt DC.
- Quiet (< 55dB), airless operation: no expensive compressed air generation required. No air consumption or air leaks to attend to. No compressed air generating environmental particulate contamination.
- Force control is precise and repeatable since there is no pressure valves, no force fluctuations caused by air pressure fluctuations.


Electric Cylinder Actuators

High speed, compact and price-competitive cylinder actuators that provide an alternative to pneumatic cylinders with superior performance. The conventional cylinder actuator shape and multiple mounting points allow the electric cylinders to be directly retrofitted in most cases. When you take into account the operating cost of compressed air, unit life expectancies, replacement costs, downtime and changeover times, SMAC's actuators often have a significantly lower total cost than air cylinders and electromechanical alternatives.

Linear:

- Stroke up to 25mm, force up to 66N, position encoder resolution 5µm standard, 1µm option.
- Programmable force, position, acceleration and velocity.
- Built-in controller type is available for simple installation and effective use of space. (See page 13)
- Optional IP65 and IP67, dust-proof and waterproof features, are available.

Electric Cylinder | CBL series



Linear and Linear Rotary Actuators



A comprehensive selection of programmable linear actuators are offered in a wide range of sizes, styles and options to satisfy your most demanding application requirements.

The precision Z-theta motion within one small actuator, providing a convenient pick, orient and place. A wide variety of linear rotary actuators are also offered with either direct drive or gearbox equipped rotary units.


Linear:

- Stroke up to 250mm, force up to 500N, position encoder resolution 5µm standard, 1 and 0.1µm option for most actuators.
- Programmable force, position, acceleration and velocity.

Rotary:

- Multi-turn servo motor, torque up to 4.5Nm, velocity up to 5000 rpm, resolution up to 132,000 increments per revolution.
- Programmable force/torque, and position.
- The vacuum passage built in the shaft through the rotary motor prevents dust build up in the unit.

Linear Rotary | LAR series



Programmability and Operating Modes

By using SMAC controllers all of our products are programmable using 3 different modes independently and controlling position, velocity, and force. This allows their performance characteristics to be tightly monitored. Pass/fail windows for any of these parameters can be set - useful for error reporting and testing applications.

Position mode

Position mode will allow the actuator to be moved to any position along the stroke using a given acceleration, velocity and force. It is possible to make absolute, relative and “learned position” moves. The force necessary to hold a given position can also be measured. This is called “holding force” and is used in applications such as switch testing.

Velocity mode

Velocity mode allows the actuator to be moved with a given velocity, acceleration, force and direction. Velocity (i.e. position vs. time) is closed-loop using feedback from the encoder, giving precise velocity control. Position and position error (the difference between actual position and desired position at a given time) can be interrogated in real time during motion. Typically used for constant speed scanning applications and Soft-Land™ routines.

Force mode

In Force mode, current in the coil is controlled to give a programmed force output. Position and velocity are open loop, using no feedback from the encoder, but actual position can still be monitored in real time. Used in applications such as tensile and compression testing.

SMAC Unique Features and Advantages

- **Fully programmable** in **Position, Acceleration, Velocity** and **Force**.
- **Soft-Land™** capability: apply controlled light force without damaging parts/material being handled.
- Direct drive = no backlash, a very high degree of accuracy & repeatability.
- Sub-micron resolution (5µm to 100nm).
- **Long operation life** = typical MTBF of over 100 million cycles.

SMAC Actuators Give You Flexibility

- Integrated position measuring system with glass scale and optical reader head (non contact).
- Ability to switch between operations - force, position and velocity mode - at any time.
- “On the fly” adjustable movement allows quick changeover.
- Constant force monitoring and control.
- Digital and analog input/output channels.
- SMAC linear motors are a servo system, hence they can be programmed to decelerate smoothly and quickly. Mechanical slamming can be totally eliminated.
- Competitively priced electric actuators that offer all of the above features and benefits.




What is a Soft-Land™?

The Soft-Land™ is a patented unique software routine which allows an SMAC actuator to approach a surface at an unknown distance and land on it with a programmed force that can be as low as 0.1N. It gives extremely accurate sensing of product location or dimensions. This is particularly useful for handling delicate or high value components, such as surface mount chips, but other uses are emerging all the time. The routine takes advantage of the SMAC actuator's unique ability to control applied force while monitoring position in real time and is available for use with all SMAC actuators.

Soft-Land™ is a patented unique capability that allows actuators to approach a surface at an unknown distance and land on it with a programmed force.

The routine consists of a controlled low force approach in velocity mode, while the position error is constantly monitored. Once contact is made the position error builds up until a pre-programmed figure is reached - resulting in the rod maintaining position on the surface of the component.



A typical Soft-Land™ routine might be as follows:

1. High speed approach in Position mode to a "safe" distance from the part.
2. Switch to Velocity mode, setting a low force and velocity.
3. Slowly approach the part, monitoring position error.
4. If position error goes outside of a programmed window, the actuator has met an obstruction (i.e. landed on the part) and the Soft-Land™ routine is completed.
5. It is also possible to set a position window where the component should be located, if it is not located within a certain position, the actuator will retract.

ELECTRIC CYLINDERS - LINEAR Stroke [mm] 10 - 25 | Peak Fore [N]: 1.5 - 190



CBL35
Stroke [mm]: 10, 15, 25
Force [N]: 8.5-22



CBL50
Stroke [mm]: 10, 25
Force [N]: 23-100



CBL35C with Built-in Controller
Stroke [mm]: 10, 15, 25
Force [N]: 8.5-22



CBL50C with Built-in Controller
Stroke [mm]: 10, 25
Force [N]: 23-100



CTL50
Stroke [mm]: 10
Force [N]: 47



CTL70
Stroke [mm]: 10
Force [N]: 190

LINEAR & LINEAR ROTARY ACTUATORS Stroke [mm] 10 - 250 | Peak Fore [N]: 2.6 - 1000



LDL15
Stroke [mm]: 10
Force [N]: 15



LDR16
Stroke [mm]: 35
Force [N]: 33



LDL25
Stroke [mm]: 10, 25, 50, 75, 100
Force [N]: 30



LDL40
Stroke [mm]: 25, 50, 75, 100
Force [N]: 90




LDL15C with Built-in Controller
Stroke [mm]: 10
Force [N]: 15



LDL25C with Built-in Controller
Stroke [mm]: 10, 25, 50, 75, 100
Force [N]: 30



LDL40C with Built-in Controller
Stroke [mm]: 25, 50, 75, 100
Force [N]: 90



LCA6
Stroke [mm]: 10
Force [N]: 3.5



LCA8
Stroke [mm]: 10, 25, 50
Force [N]: 2.6 - 4



LCA13 / LCR13
Stroke [mm]: 25, 35, 50
Force [N]: 7 - 14



LCA16 / LCR16
Stroke [mm]: 10 - 50
Force [N]: 7 - 14



LCA20 / LCR20
Stroke [mm]: 25
Force [N]: 25



LCA25
Stroke [mm]: 10 - 200
Force [N]: 7.4 - 22



LCA32
Stroke [mm]: 12
Force [N]: 76



LCA50
Stroke [mm]: 25 - 250
Force [N]: 45 - 130




Linear rotary motion within one actuator.



LBL25
Stroke [mm]: 25, 50,
75, 100
Force [N]: 70



LBL40/LBR40
Stroke [mm]: 50
Force [N]: 100



LBL600
Stroke [mm]: 35
Force [N]: 1000



MLA8/MSA8
Stroke [mm]: 10
Force [N]: 4



LAR31
Stroke [mm]: 30, 50
Force [N]: 11, 20



LAL35 / LAR35
Stroke [mm]: 25, 50, 100
Force [N]: 6 - 31.5



LAL55 / LAR55
Stroke [mm]: 50, 100, 150
Force [N]: 13 - 40



LAL95 / LAR95
Stroke [mm]: 15, 25, 50
Force [N]: 65 - 195



LAL300 / LAR300
Stroke [mm]: 30, 50, 100
Force [N]: 80 - 250



LAL500
Stroke [mm]: 25, 50
Force [N]: 500


LINEAR SLIDE ACTUATORS Stroke [mm] 5 - 250 | Peak Force [N]: 2.1 - 202



LCS8
Stroke [mm]: 10, 25, 50
Force [N]: 2.6-4



LCS25
Stroke [mm]: 10-200
Force [N]: 7.4-22



LCS50
Stroke [mm]: 25-250
Force [N]: 45-90



LBS17
Stroke [mm]: 5
Force [N]: 13.5




SLA10
Stroke [mm]: 5, 10
Force [N]: 2.1



SLA25
Stroke [mm]: 10
Force [N]: 4



LAS35
Stroke [mm]: 25, 50, 100
Force [N]: 6-31.5



LAS55
Stroke [mm]: 50, 100, 150
Force [N]: 13-40



LAS95
Stroke [mm]: 15, 25, 50
Force [N]: 65-185



LAS300
Stroke [mm]: 50
Force [N]: 202

GRIPPERS & XY STAGES Stroke [mm] 10 - 30 | Peak Force [N]: 3.1 - 45



MGR7
Stroke [mm]: 10
Force [N]: 3.8



GRP20
Stroke [mm]: 10
Force [N]: 8



GRP35
Stroke [mm]: 30
Force [N]: 25, 26



GRP50
Stroke [mm]: 30
Force [N]: 35, 45



LXY15
Stroke [mm]: 15
Force [N]: 22



LXY25
Stroke [mm]: 25
Force [N]: 42

CONTROLLERS & AMPLIFIERS



VLCI-R3
Built-in type Single-axis
Controller/servo Driver



VLCI-X1
Single-axis DC brushed/
brushless controller



VLC-1-07/13
Single-axis DC Brushed/
Brushless Controller



VLC-ETC
Single-axis EtherCAT
Controller/Servo Driver



VLCI-CAN-07
Single-axis CANOpen
Controller/Servo Driver



VLC-25-07/13
Dual-axis Controller/
Servo Driver



VLC-E-EIP
Dual-axis Ethernet/IP
Controller/Servo Driver



MIOE-8/8
Expansion I/O module
for LAC-1 and LAC-25

ENCODERS - LINEAR & ROTARY



LL Series
Linear Encoder
Resolution [μm]: 5, 1



SLE-LI Series
Linear Encoder
Resolution [μm]: 1, 0.5, 0.1



SLE-35 Series
Linear Encoder
Resolution [μm]: 0.1, 0.05



SRE-30 Series
Rotary Encoder
Resolution [CPR]: 1K, 2K, 4K, 8K, 16K

HT MOTOR - HIGH TORQUE BUSHLESS 3-PHASE DC MOTOR




HT35 Series
Voltage [VDC]: 48
Power [W]: 26



HT55 Series
Voltage [VDC]: 48
Power [W]: 37.8

PART NUMBERING SYSTEM



Part Number Examples

CBL35C-010-75-1-F3

CBL35 series electric cylinder with built-in controller, 10mm stroke, 48volt single phase, 5 micron encoder, single coil, female shaft end, and flying lead

LCA25-200-31-6-F3

LCA25 series linear actuator, 200mm stroke, 48volt multi phase, 1 micron encoder, 6-coil, female shaft end, and flying lead

Notes

- Series will not have leading zeros (e.g. CBL35)
- Stroke must include zeros (e.g. 050)
- Spring must be specified as full return or counter balance, payload and orientation (vertical or horizontal). Mod number will be assigned for non-standard spring specification.

SMAC Actuators' Unique Features



Soft-Land™

A patented capability to apply controlled light force without damaging parts/materials being handled.



Feedback

Built-in sensing that can report if the desired work was accomplished or not. It can be used for Data Acquisition.



Linear Rotary Motion

The precision Z-theta motion within one small compact actuator, providing convenient pick, orient, and place movements.



IP Protection

Optional IP65 and IP67, dustproof and waterproof features.



Graphical User Interface (GUI)

SMAC GUI provides a simple and straightforward way to quickly configure motion parameters of a variety of SMAC actuators and controllers. Application-based GUIs are also available.

Direct replacement of air cylinders. High speed, compact and price-competitive cylinder actuators are the ideal solution for new machine designs and upgrade.



- ✓ Direct replacement of air cylinders
- ✓ Cost competitive
- ✓ Long life expectancy, typically over 100 million cycles
- ✓ IP protection optional

| Part Number | Voltage [DC] | Size: Dia.x L [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|--------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| CBL35-010-55-1 | 24 | Ø35x96 | 10 | 15 | 6 | 9 | 1.5 | 0.04 | 0.45 |
| CBL35-010-75-1 | 48 | Ø35x96 | 10 | 22 | 8.8 | 13.4 | 1.6 | 0.04 | 0.45 |
| CBL35-015-55-1 | 24 | Ø35x101 | 15 | 10 | 4 | 7 | 1.5 | 0.06 | 0.5 |
| CBL35-015-75-1 | 48 | Ø35x101 | 15 | 14 | 5.6 | 8.8 | 1.6 | 0.06 | 0.5 |
| CBL35-025-55-1 | 24 | Ø35x111 | 25 | 8.5 | 3.4 | 5.8 | 1.5 | 0.06 | 0.6 |
| CBL35-025-75-1 | 48 | Ø35x111 | 25 | 14 | 5.6 | 8.8 | 1.6 | 0.06 | 0.6 |
| CBL50-010-55-1 | 24 | Ø50x123 | 10 | 33 | 13 | 22 | 1.5 | 0.14 | 1.14 |
| CBL50-010-55-2 | 24 | Ø50x166 | 10 | 49 | 19 | 16 | 3 | 0.21 | 1.7 |
| CBL50-010-75-1 | 48 | Ø50x123 | 10 | 40 | 16 | 26 | 1.5 | 0.14 | 1.14 |
| CBL50-010-75-2 | 48 | Ø50x166 | 10 | 100 | 40 | 33 | 3 | 0.21 | 1.7 |
| CBL50-025-55-1 | 24 | Ø50x138 | 25 | 23 | 9 | 15 | 1.5 | 0.15 | 1.3 |
| CBL50-025-55-2 | 24 | Ø50x203 | 25 | 40 | 16 | 13 | 3 | 0.24 | 2.1 |
| CBL50-025-75-1 | 48 | Ø50x138 | 25 | 40 | 16 | 26 | 1.5 | 0.15 | 1.3 |
| CBL50-025-75-2 | 48 | Ø50x203 | 25 | 70 | 28 | 23 | 3 | 0.24 | 2.1 |
| CTL50-010-75-2 | 48 | Ø48x160 | 10 | 47 | 18 | 12.7 | 3 | 0.19 | 1.1 |
| CTL70-010-75-2 | 48 | Ø70x190 | 10 | 190 | 76 | 21 | 9 | 0.35 | 3 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



Options & Modifications (Consult factory for availability)

| | | |
|---------------------|-------|---|
| Encoder resolutions | ----- | 5µm standard. 1µm optional. |
| Shaft ends | ----- | Male, Female, Blank and Custom. |
| Return spring | ----- | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | ----- | Vacuum through the shaft or on the shaft for pick and place applications. |
| Mount | ----- | Front mount (standard), base mount optional. Threaded Mount is available for CAL12 series only. |
| Dust/Waterproof | ----- | IP65/67 protection is available with CBL series. |

SMAC Moving Coil Actuators

ELECTRIC CYLINDERS WITH BUILT-IN CONTROLLER

A complete self-contained unit, suggested for replacement of pneumatic cylinders where increased lifetime, speed and control are desirable.



- ✓ Built-in controller
- ✓ Airless and quiet operation
- ✓ Graphical User Interface for simple set-up
- ✓ IP protection optional

| Part Number | Voltage [DC] | Size: Dia x L [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constance [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|-----------------|--------------|--------------------|-------------|----------------|----------------------|-----------------------|-----------------------|------------------|-------------|
| CBL35C-010-55-1 | 24 | Ø35x135 | 10 | 15 | 6 | 9 | 1.5 | 0.04 | 0.52 |
| CBL35C-010-75-1 | 48 | Ø35x135 | 10 | 22 | 8.8 | 13.4 | 1.6 | 0.04 | 0.52 |
| CBL35C-015-55-1 | 24 | Ø35x140 | 15 | 10 | 4 | 7 | 1.5 | 0.06 | 0.57 |
| CBL35C-015-75-1 | 48 | Ø35x140 | 15 | 14 | 5.6 | 8.8 | 1.6 | 0.06 | 0.57 |
| CBL35C-025-55-1 | 24 | Ø35x150 | 25 | 8.5 | 3.4 | 5.8 | 1.5 | 0.06 | 0.67 |
| CBL35C-025-75-1 | 48 | Ø35x150 | 25 | 14 | 5.6 | 8.8 | 1.6 | 0.06 | 0.67 |
| CBL50C-010-55-1 | 24 | Ø50x177.5 | 10 | 33 | 13 | 22 | 1.5 | 0.14 | 1.29 |
| CBL50C-010-55-2 | 24 | Ø50x220.5 | 10 | 49 | 19 | 16 | 3 | 0.21 | 1.8 |
| CBL50C-010-75-1 | 48 | Ø50x177.5 | 10 | 40 | 16 | 26 | 1.5 | 0.14 | 1.29 |
| CBL50C-010-75-2 | 48 | Ø50x220.5 | 10 | 100 | 40 | 33 | 3 | 0.21 | 1.8 |
| CBL50C-025-55-1 | 24 | Ø50x192.5 | 25 | 23 | 9 | 15 | 1.5 | 0.15 | 1.38 |
| CBL50C-025-55-2 | 24 | Ø50x258 | 25 | 40 | 16 | 13 | 3 | 0.24 | 2.25 |
| CBL50C-025-75-1 | 48 | Ø50x192.5 | 25 | 40 | 16 | 26 | 1.5 | 0.15 | 1.38 |
| CBL50C-025-75-2 | 48 | Ø50x255.5 | 25 | 70 | 28 | 23 | 3 | 0.24 | 2.25 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



CBL35C



CBL50C



Options & Modifications (Consult factory for availability)

| | |
|---------------------|---|
| Built-in Controller | Simple installation and effective use of space. |
| Encoder resolutions | 5µm standard. 1µm optional. |
| Shaft ends | Male, Female, Blank and Custom. |
| Return spring | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | Vacuum through the shaft or on the shaft for pick and place applications. |
| Mount | Front mount only |
| Dust/Waterproof | IP65/67 protection is available. |
| Cable | Flying lead only |

The LDL series has been designed as a cost-competitive alternative to pneumatics. The LDL is fully programmable in force, acceleration, position and velocity. It allows you to change product profiles on the fly.



- ✓ Cost competitive
- ✓ Fully programmable in force, position and velocity
- ✓ Graphical User Interface for simple programming

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LDL15-010-35-3 | 48 | 110x15x70 | 10 | 15 | 6 | 4.4 | 3.4 | 0.07 | 0.5 |
| LDL25-010-35-6 | 48 | 155x25.4x63.5 | 10 | 30 | 12 | 8.4 | 3.6 | 0.1 | 0.9 |
| LDL25-025-35-6 | 48 | 155x25.4x63.5 | 25 | 30 | 12 | 8.4 | 3.6 | 0.1 | 0.9 |
| LDL25-050-35-6 | 48 | 180x25.4x63.5 | 50 | 30 | 12 | 8.4 | 3.6 | 0.11 | 1.1 |
| LDL25-075-35-6 | 48 | 220x25.4x63.5 | 50 | 30 | 12 | 40 | 3.6 | 0.12 | 1.3 |
| LDL25-100-35-6 | 48 | 260x25.4x63.5 | 10 | 30 | 12 | 8.4 | 3.6 | 0.13 | 1.6 |
| LDL40-025-35-3 | 48 | 190x40x120 | 25 | 90 | 36 | 40 | 2.5 | 0.45 | 4 |
| LDL40-050-35-3 | 48 | 190x40x120 | 50 | 90 | 36 | 40 | 2.5 | 0.47 | 4 |
| LDL40-075-35-3 | 48 | 225x40x120 | 75 | 90 | 36 | 40 | 2.5 | 0.49 | 4.5 |
| LDL40-100-35-3 | 48 | 250x40x120 | 100 | 90 | 36 | 40 | 2.5 | 0.51 | 5.2 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



Options & Modifications (Consult factory for availability)

| | | |
|-------------------------------------|-------|---|
| Linear encoder resolutions | ----- | 5µm standard and 1µm optional. |
| Shaft ends | ----- | Male, Female, Blank and Custom (check availability of custom option). |
| Return spring | ----- | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | ----- | Vacuum through the shaft or on the shaft for pick and place applications. |
| Increase of force accuracy/lifetime | ----- | Low-friction linear guide/extra-long preload linear guide. |

LINEAR ACTUATORS WITH BUILT-IN CONTROLLER

Cost-competitive electric actuator, LDL series is offered with an integrated controller. This makes the LDL an economical, space saving solution.



- ✓ Built-in Controller
- ✓ Cost competitive
- ✓ Fully programmable in force, position and velocity
- ✓ Graphical User Interface for simple programming

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|-----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LDL15C-010-35-3 | 48 | 160x15x70 | 10 | 15 | 6 | 4.4 | 3.4 | 0.075 | 0.68 |
| LDL25C-010-35-6 | 48 | 180x25.4x63.5 | 10 | 30 | 12 | 8.4 | 3.6 | 0.1 | 1.1 |
| LDL25C-025-35-6 | 48 | 180x25.4x63.5 | 25 | 30 | 12 | 8.4 | 3.6 | 0.1 | 1.1 |
| LDL25C-050-35-6 | 48 | 220x25.4x63.5 | 50 | 30 | 12 | 8.4 | 3.6 | 0.11 | 1.3 |
| LDL25C-075-35-6 | 48 | 260x25.4x63.5 | 50 | 30 | 12 | 40 | 3.6 | 0.12 | 1.5 |
| LDL25C-100-35-6 | 48 | 300x25.4x63.5 | 10 | 30 | 12 | 8.4 | 3.6 | 0.13 | 1.7 |
| LDL40C-025-35-3 | 48 | 190x40x120 | 25 | 90 | 36 | 40 | 2.5 | 0.45 | 4 |
| LDL40C-050-35-3 | 48 | 225x40x120 | 50 | 90 | 36 | 40 | 2.5 | 0.47 | 4 |
| LDL40C-075-35-3 | 48 | 250x40x120 | 75 | 90 | 36 | 40 | 2.5 | 0.49 | 4.5 |
| LDL40C-100-35-3 | 48 | 285x40x120 | 100 | 90 | 36 | 40 | 2.5 | 0.51 | 5.2 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



Options & Modifications (Consult factory for availability)

- Built-in Controller ----- Simple installation and effective use of space.
- Linear encoder resolutions ----- 5µm standard and 1µm optional.
- Shaft ends ----- Male, Female, Blank and Custom (check availability of custom option).
- Return spring ----- Prevents the shaft from dropping during vertical operation when power is cut.
- Vacuum ----- Vacuum through the shaft or on the shaft for pick and place applications.
- Increase of force accuracy/lifetime ----- Low-friction linear guide/extra-long preload linear guide.

Developed as next generation servo motor based on moving coil technology. Snap-Together design controls tight tolerance stack-up to assure high product quality at a competitive price.



- ✓ Cost effective
- ✓ Built-in lubrication for long operation life
- ✓ High cycle and acceleration
- ✓ IP protection optional

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LCA6-010-55-3 | 24 | 135x60x6 | 10 | 3.5 | (*) | 2.9 | 1.2 | 0.037 | 0.21 |
| LCA8-010-55-2 | 24 | 95x50x8 | 10 | 4 | (*) | 3.2 | 1.7 | 0.025 | 0.16 |
| LCA8-025-15-3 | 24 | 110x50x8 | 25 | 2.6 | (*) | 2.2 | 1.3 | 0.027 | 0.18 |
| LCA8-050-15-3 | 24 | 135x50x8 | 50 | 2.6 | (*) | 2.2 | 1.3 | 0.03 | 0.22 |
| LCA13-025-55-2 | 24 | 155x75x13 | 25 | 7 | 2.8 | 2.5 | 3 | 0.08 | 0.4 |
| LCA13-035-15-6 | 24 | 180x75x13 | 35 | 14 | 5.6 | 9.4 | 1.5 | 0.12 | 0.52 |
| LCA13-050-15-6 | 24 | 210x75x13 | 50 | 14 | 5.6 | 9.4 | 1.5 | 0.125 | 0.6 |
| LCA16-010-55-2 | 24 | 110x60x16 | 10 | 6 | 2.5 | 4.3 | 1.5 | 0.045 | 0.435 |
| LCA16-010-75-2 | 48 | 110x60x16 | 10 | 13 | 5 | 6.5 | 1.5 | 0.045 | 0.435 |
| LCA16-025-55-2 | 24 | 155x75x16 | 25 | 7 | 2.8 | 2.5 | 3 | 0.08 | 0.47 |
| LCA16-035-15-6 | 24 | 180x75x16 | 35 | 14 | 5.6 | 9.4 | 1.5 | 0.12 | 0.62 |
| LCA16-050-15-6 | 24 | 210x75x16 | 50 | 14 | 5.6 | 9.4 | 1.5 | 0.125 | 0.73 |
| LCA20-025-55-2 | 24 | 155x75x20 | 25 | 9 | 3.6 | 3 | 3 | 0.08 | 0.71 |
| LCA20-025-75-2 | 48 | 155x75x20 | 25 | 25 | 10 | 7 | 3.6 | 0.08 | 0.71 |
| LCA25-010-55-1 | 24 | 70x55x25 | 10 | 8 | 3 | 6 | 1.5 | 0.04 | 0.27 |
| LCA25-010-55-2 | 24 | 130x60x25 | 10 | 16 | 6 | 5.5 | 3 | 0.085 | 0.45 |
| LCA25-010-75-1 | 48 | 70x55x25 | 10 | 12 | 5 | 8 | 1.5 | 0.04 | 0.27 |
| LCA25-010-75-2 | 48 | 130x60x25 | 10 | 22 | 9 | 8 | 3 | 0.085 | 0.45 |
| LCA25-025-15-6 | 24 | 130x60x25 | 25 | 15 | 6 | 13 | 1.6 | 0.076 | 0.55 |
| LCA25-025-35-6 | 48 | 130x60x25 | 25 | 20.5 | 8.2 | 14.5 | 1.6 | 0.076 | 0.55 |
| LCA25-025-55-2 | 24 | 130x60x25 | 25 | 7.4 | 2.9 | 2.5 | 3 | 0.076 | 0.55 |
| LCA25-025-75-2 | 48 | 130x60x25 | 25 | 9.2 | 3.6 | 3 | 3 | 0.076 | 0.55 |
| LCA25-050-15-6 | 24 | 155x60x25 | 50 | 15 | 6 | 13 | 1.6 | 0.082 | * |
| LCA25-050-35-6 | 48 | 155x60x25 | 50 | 20.5 | 8.2 | 14.5 | 1.6 | 0.082 | * |
| LCA25-100-15-6 | 24 | 205x60x25 | 100 | 15 | 6 | 13 | 1.6 | 0.1 | * |
| LCA25-100-35-6 | 48 | 205x60x25 | 100 | 20.5 | 8.2 | 14.5 | 1.6 | 0.1 | * |
| LCA25-150-15-6 | 24 | 258x60x25 | 150 | 15 | 6 | 13 | 1.6 | 0.12 | * |
| LCA25-150-35-6 | 48 | 258x60x25 | 150 | 20.5 | 8.2 | 14.5 | 1.6 | 0.12 | * |
| LCA25-200-15-6 | 24 | 310x60x25 | 200 | 15 | 6 | 13 | 1.6 | 0.14 | 1.3 |
| LCA25-200-35-6 | 48 | 310x60x25 | 200 | 20.5 | 8.2 | 14.5 | 1.6 | 0.14 | 1.3 |

SMAC Moving Coil Actuators

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LCA32-012-75-3 | 48 | 100x57x31 | 12 | 76 | 30 | 13 | 6 | 0.076 | 0.75 |
| LCA50-010-75-2 | 48 | 125x50x100 | 10 | 130 | 50 | 46 | 2.8 | 0.43 | 2.6 |
| LCA50-025-75-1 | 48 | 125x100x50 | 25 | 50 | 20 | 40 | 1.5 | 0.335 | 2.16 |
| LCA50-050-35-6 | 48 | 250x115x50 | 50 | 90 | 36 | 67 | 1.7 | 0.665 | * |
| LCA50-050-75-1 | 48 | 125x100x50 | 50 | 45 | 18 | 30 | 1.6 | 0.335 | 2.58 |
| LCA50-050-75-2 | 48 | 215x100x50 | 50 | 85 | 34 | 30 | 3 | 0.465 | 4.34 |
| LCA50-100-35-6 | 48 | 300x115x50 | 100 | 90 | 36 | 67 | 1.7 | 0.66 | 5.7 |
| LCA50-150-35-6 | 48 | 350x115x50 | 150 | 90 | 36 | 67 | 1.7 | 0.825 | 8 |
| LCA50-250-35-6 | 48 | 450x115x50 | 250 | 90 | 36 | 67 | 1.7 | 1 | 14 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. Linear actuators are also available as linear slides (see page 20). (*)Consult factory



LCA6



LCA8



LCA13



LCA16/LCA20



LCA25



LCA32



LCA50



Options & Modifications (Consult factory for availability)

| | |
|-------------------------------------|---|
| Linear encoder resolutions | 5µm standard. 1µm and 0.1µm optional for most units. Consult factory for availability. |
| Shaft ends | Male, Female, Blank and Custom (check availability of custom option). |
| Return spring | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | Vacuum through the shaft or on the shaft for pick and place applications. |
| Extended nose bushing | For tighter shaft run-out and higher side load onto the shaft. |
| Increase of force & acceleration | 48 volt coil and double coil options are available for some units with 24 volt single coil. |
| Increase of force accuracy/lifetime | Low-friction linear guide/extra-long preload linear guide. |
| Dust/Waterproof | IP65/67 protection is available with LCA50 series. |

The LBL is price competitive solutions for some higher force applications, previously dominated by pneumatic actuators.

The MLA and MSA gauge actuators provide you gauging solutions with consistent, fast and precise control of the process.



- ✓ High force and acceleration
- ✓ Cost effective
- ✓ Far better Gage R&R (Repeatability and Reproducibility)

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|-----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LBL25-025-35-3 | 48 | 175x127x25 | 25 | 70 | 28 | 31.2 | 2.5 | 0.19 | - |
| LBL25-050-35-3 | 48 | 200x127x25 | 50 | 70 | 28 | 31.2 | 2.5 | 0.19 | - |
| LBL25-100-35-3 | 48 | 280x127x25 | 100 | 70 | 28 | 31.2 | 2.5 | 0.19 | 2 |
| LBL25-150-35-3 | 48 | 310x127x25 | 150 | 70 | 28 | 31.2 | 2.5 | 0.19 | 3.8 |
| LBL25-200-35-3 | 48 | 360x127x25 | 200 | 70 | 28 | 31.2 | 2.5 | 0.21 | 4.56 |
| LBL40-050-35-3 | 48 | 335x160x40 | 50 | 100 | 40 | 40 | 2.5 | 0.9 | 7.2 |
| LBL600-035-75-6 | 48 | 280x245x86 | 35 | 1000 | 400 | 50 | 20 | 2.3 | 30 |
| MLA8-010-51-2 | 24 | 95x50x8 | 10 | 4 | (*) | 3.2 | (*) | 0.025 | 0.17 |
| MSA8-010-01-0 | 5 - 15 | 95x28x8 | 10 | (*) | (*) | (*) | (*) | 0.011 | 0.054 |


NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. (*) Consult factory.



LBL25



LBL40



LBL600



MLA8



MSA8

Gauging Actuator

Options & Modifications (Consult factory for availability)

- Linear encoder resolutions ----- 5µm standard and 1µm optional.
- Shaft ends ----- Male, Female, Blank and Custom (check availability of custom option).
- Return spring ----- Prevents the shaft from dropping during vertical operation when power is cut.
- Vacuum ----- Vacuum through the shaft or on the shaft for pick and place applications.
- Extended nose bushing ----- For tighter shaft run-out and higher side load onto the shaft.
- Increase of force accuracy/lifetime ----- Low-friction linear guide/extra-long preload linear guide.

SMAC's original series of linear actuators with stroke up to 150mm and a peak force of up to 500N. As with all SMAC actuators, the LAL has independent control of position, speed, and force.




- ✓ Soft-Land™ capability and precise force control
- ✓ High cycle
- ✓ Data feedback

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|-----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LAL35-025-55-2 | 24 | 135x90x35 | 25 | 31.5 | 12.6 | 15.5 | 2.9 | 0.19 | 1.06 |
| LAL35-025-75-1 | 48 | 135x90x35 | 25 | 18 | 7 | 10 | 1.3 | 0.12 | 0.95 |
| LAL35-050-55-1 | 24 | 135x90x35 | 50 | 10 | 4 | 7 | 1.6 | 0.13 | 1.1 |
| LAL35-050-75-1 | 48 | 135x90x35 | 50 | 12.5 | 5 | 10 | 1.3 | 0.13 | 1.1 |
| LAL35-100-55-1 | 24 | 135x90x35 | 100 | 6 | 2.4 | 3.5 | 1.6 | 0.1 | 1.7 |
| LAL55-050-55-1 | 24 | 250x110x55 | 50 | 25 | 10 | 19 | 1.3 | 0.3 | 3 |
| LAL55-050-75-1 | 48 | 250x110x55 | 50 | 40 | 16 | 24.5 | 1.8 | 0.3 | 3 |
| LAL55-100-55-1 | 24 | 250x110x55 | 100 | 16 | 6.4 | 13 | 1.3 | 0.3 | 3.8 |
| LAL55-100-75-1 | 48 | 250x110x55 | 100 | 25 | 10 | 17 | 1.8 | 0.3 | 3.8 |
| LAL55-150-55-1 | 24 | 250x110x55 | 150 | 13 | 5 | 10 | 1.3 | 0.4 | 4.5 |
| LAL55-150-75-1 | 48 | 250x110x55 | 150 | 19.5 | 8 | 12.5 | 1.8 | 0.4 | 4.5 |
| LAL95-015-75-1 | 48 | 90x70x95 | 15 | 84 | 33 | 53 | 1.7 | 0.25 | 2.2 |
| LAL95-015-75-2 | 48 | 147x70x95 | 15 | 185 | 74 | 58 | 3.2 | 0.5 | 3 |
| LAL95-025-75-2 | 48 | 180x70x95 | 25 | 162 | 65 | 52 | 3.1 | 0.58 | 3.75 |
| LAL95-050-75-1 | 48 | 147x70x95 | 50 | 65 | 26 | 41 | 1.7 | 0.25 | 3 |
| LAL300-030-75-1 | 48 | 120x85x120 | 30 | 115 | 46 | 76 | 1.6 | 0.45 | 4.8 |
| LAL300-030-75-2 | 48 | 210x85x120 | 30 | 250 | 100 | 87.3 | 3 | 0.8 | 7.8 |
| LAL300-050-75-2 | 48 | 210x85x120 | 50 | 202 | 80 | 86 | 3 | 0.8 | 8.8 |
| LAL300-100-75-1 | 48 | 210x85x120 | 100 | 80 | 32 | 43 | 2 | 0.7 | 7.9 |
| LAL500-025-75-2 | 48 | 300x140x200 | 25 | 500 | 200 | 166 | 3 | 1.6 | 26.5 |
| LAL500-050-75-2 | 48 | 300x140x200 | 50 | 500 | 200 | 100 | 4 | 1.6 | 26.5 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. Linear actuators are also available as linear slides (see page 21)



LAL35



LAL55



LAL95



LAL300



LAL500

Options & Modifications (Consult factory for availability)

| | |
|-------------------------------------|---|
| Linear encoder resolutions | 5µm standard. 1µm and 0.1µm optional for most units. Consult factory for availability. |
| Shaft ends | Male, Female, Blank and Custom (check availability of custom option). |
| Return spring | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | Vacuum through the shaft or on the shaft for pick and place applications. |
| Extended nose bushing | For tighter shaft run-out and higher side load onto the shaft. |
| Increase of force & acceleration | 48 volt coil and double coil options are available for some units with 24 volt single coil. |
| Increase of force accuracy/lifetime | Low-friction linear guide/extra-long preload linear guide. |
| Dust/Waterproof | IP65/67 protection is available with LAL95 series. |

LINEAR ROTARY ACTUATORS

LBR/LCR/LDR SERIES

The LBR and LCR are slim, stackable Z-theta actuators. The LDR, precise, lower-cost linear rotary actuator, features SMAC HT motor.



- ✓ Independent linear and rotary motions in one unit
- ✓ Absolute control over force/torque, position, acceleration and velocity
- ✓ Direct drive brushless servo motor
- ✓ Vacuum through shaft prevents dust accumulation

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] | Peak Torque* [Nm] | Rotary type | Rotary Encoder Resolution | Velocity* [rpm] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|-------------------|-------------|---------------------------|-----------------|
| LBR40-050-35-3 | 48 | 335x160x40 | 50 | 100 | 40 | 40 | 2.5 | 0.9 | 7.2 | 0.45 | direct | 2K | 2100 |
| LBR62-050-35-3 | 48 | 360x165x62 | 50 | 100 | 40 | 40 | 2.5 | 1.9 | 8.5 | 2.2 | direct | 2K | 500/750 |
| LBR62-150-35-3 | 48 | 460x165x62 | 150 | 100 | 40 | 40 | 2.5 | 2 | 11.1 | 2.2 | direct | 2K | 500/750 |
| LBR62-300-35-3 | 48 | 610x165x62 | 300 | 100 | 40 | 40 | 2.5 | 2.1 | 14.3 | 2.2 | direct | 2K | 500/750 |
| LCR13-025-55-2 | 24 | 155x75x13 | 25 | 7 | 2.8 | 2.5 | 3 | 0.11 | 0.43 | 0.047 | direct | 24K | 1K |
| LCR13-035-15-6 | 24 | 180x75x13 | 35 | 14 | 5.6 | 9.4 | 1.5 | 0.15 | 0.55 | 0.047 | direct | 24K | 1K |
| LCR13-050-15-6 | 24 | 210x75x13 | 50 | 14 | 5.6 | 9.4 | 1.5 | 0.155 | 0.62 | 0.047 | direct | 24K | 1K |
| LCR16-025-55-2 | 24 | 155x75x16 | 25 | 7 | 2.5 | 2.5 | 3 | 0.11 | 0.5 | 0.047 | direct | 24K | 1K |
| LCR16-035-15-6 | 24 | 180x75x16 | 35 | 14 | 5.6 | 9.4 | 1.5 | 0.15 | 0.65 | 0.047 | direct | 24K | 1K |
| LCR16-050-15-6 | 24 | 210x75x16 | 50 | 14 | 5.6 | 9.4 | 1.5 | 0.155 | 0.75 | 0.047 | direct | 24K | 1K |
| LCR20-025-75-2 | 48 | 155x75x20 | 25 | 25 | 10 | 7 | 3.6 | 0.095 | 0.65 | 0.047 | direct | 24K | 1K |
| LDR16-035-15-6 | 24 | 190x16x75 | 35 | 14 | 5.6 | 9.4 | 1.5 | 0.15 | 0.65 | 0.033 | direct | 24K | 1K |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



LBR40



LBR62



LCR13



LCR16/LCR20



LDR16

Options & Modifications (Consult factory for availability)

| | |
|-------------------------------------|---|
| Linear encoder resolutions | 5µm standard. 1µm optional. |
| Shaft ends | Male, Female, Blank and Custom (check availability of custom option). |
| Return spring | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | For pick and place applications. |
| Extended nose bushing | For tighter shaft run-out and higher side load onto the shaft. |
| Increase of force & acceleration | 48 volt coil and double coil options are available for some units with 24 volt single coil. |
| Increase of torque/gear ratio | Alternative geared motors are available for some units. |
| Rotary encoder resolution | Consult factory for higher resolution. |
| Increase of force accuracy/lifetime | Low-friction linear guide/extra-long preload linear guide. |
| M12 connector | Option available with CBR series |

SMAC Moving Coil Actuators

The precision Z-theta motion within one small actuator, providing a convenient pick, orient and place.




- ✓ Soft-Land™ function and precise force/torque control
- ✓ Precision positioning
- ✓ Vacuum built-in through the shaft

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] | Peak Torque* [Nm] | Rotary Type | Rotary Encoder Resolution | Velocity* [rpm] |
|-----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|-------------------|--------------------|---------------------------|-----------------|
| LAR31-030-55-1 | 24 | 140x80x34.7 | 30 | 11 | 4.4 | 7 | 1.5 | 0.19 | 0.84 | 0.06 | direct | 40960 | 2000 |
| LAR31-050-15-6 | 24 | 175x78.8x36.4 | 50 | 20 | 8 | 8.5 | 3.5 | 0.25 | 1 | 0.06 | | 40960 | 2000 |
| LAR35-025-55-1 | 24 | 190x90x35 | 25 | 12 | 4.8 | 7.5 | 1.6 | 0.32 | 1.55 | 0.085 | | 20K | 75 - 5000 |
| LAR35-050-55-1 | 24 | 190x90x35 | 50 | 10 | 4 | 7 | 1.6 | 0.29 | 1.4 | 0.085 | direct or gear box | 20K | 500 - 5000 |
| LAR51-058-35-6 | 48 | 180x95.6x54 | 58 | 41 | 16.4 | 11.5 | 6 | 0.35 | 2.1 | 0.14 | | 40960 | 2000 |
| LAR55-050-55-1 | 24 | 250x110x55 | 50 | 25 | 10 | 19 | 1.6 | 0.5 | 3.1 | 0.2 - 2.5 | | 2K - 28K | 500 - 5000 |
| LAR55-050-75-1 | 48 | 250x110x55 | 50 | 40 | 16 | 27 | 1.8 | 0.31 | 2.8 | 0.2 - 2.5 | | 2K - 28K | 500 - 5000 |
| LAR55-100-55-1 | 24 | 250x110x55 | 100 | 16 | 6.4 | 13 | 1.6 | 0.5 | 3.85 | 0.2 - 2.5 | | 2K - 28K | 500 - 5000 |
| LAR55-100-75-1 | 48 | 250x110x55 | 100 | 25 | 10 | 13 | 2 | 0.5 | 3.85 | 0.2 - 2.5 | | 2K - 28K | 500 - 5000 |
| LAR95-015-75-1 | 48 | 304x115x90 | 15 | 84 | 33 | 53 | 1.7 | 0.9 | 3.5 | 0.2 - 4.5 | | 2K - 132K | 75 - 5000 |
| LAR95-050-75-1 | 48 | 304x115x90 | 50 | 65 | 26 | 41 | 1.7 | 0.93 | 4.2 | 0.2 - 4.5 | | 2K | 75 - 5000 |
| LAR300-050-75-2 | 48 | 284x160x85 | 50 | 202 | 80 | 86 | 3 | 1 | 9.5 | 0.2 - 4.5 | | 2K - 132K | 75 - 5000 |
| LAR300-100-75-1 | 48 | 291x160x85 | 100 | 80 | 32 | 43 | 4 | 1.69 | 10.7 | 0.2 - 4.5 | | 2K - 132K | 75 - 5000 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.




LAR31



LAR35



LAR51



LAR55



LAR95



LAR300

Options & Modifications (Consult factory for availability)

| | |
|-------------------------------------|---|
| Linear encoder resolutions | 5µm standard. 1µm and 0.1µm optional for most units. Consult factory for availability. |
| Shaft ends | Male, Female, Blank and Custom (check availability of custom option). |
| Return spring | Prevents the shaft from dropping during vertical operation when power is cut. |
| Vacuum | For pick and place applications. |
| Extended nose bushing | For tighter shaft run-out and higher side load onto the shaft. |
| Increase of force & acceleration | 48 volt coil and double coil options are available for some units with 24 volt single coil. |
| Increase of torque/gear ratio | Alternative geared motors are available for some units. |
| Rotary encoder resolution | Consult factory for higher resolution. |
| Increase of force accuracy/lifetime | Low-friction linear guide/extra-long preload linear guide. |

*Peak Torque and Velocity can vary based on your specific application.

The LCS is designed based on the LCA series with stroke up to 250mm, and peak force up to 90N.



- ✓ High/low speed and precise positioning with high repeatability
- ✓ Ideal for parts feeding, scanning, testing
- ✓ Soft-Land™ capability

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LCS8-010-55-2 | 24 | 95x50x8 | 10 | 4 | (*) | 3.2 | 1.7 | 0.025 | 0.16 |
| LCS8-025-15-3 | 24 | 110x50x8 | 25 | 2.6 | (*) | 2.2 | 1.3 | 0.025 | 0.17 |
| LCS8-050-15-3 | 24 | 135x50x8 | 50 | 2.6 | (*) | 2.2 | 1.3 | 0.025 | 0.21 |
| LCS25-010-55-1 | 24 | 70x55x25 | 10 | 8 | 3 | 6 | 1.5 | 0.04 | 0.27 |
| LCS25-010-55-2 | 24 | 130x60x25 | 10 | 16 | 6 | 5.5 | 3 | 0.085 | 0.45 |
| LCS25-010-75-1 | 48 | 70x55x25 | 10 | 12 | 4.8 | 8 | 1.5 | 0.04 | 0.27 |
| LCS25-010-75-2 | 48 | 130x60x25 | 10 | 22 | 8 | 8 | 3 | 0.085 | 0.45 |
| LCS25-025-15-6 | 24 | 130x60x25 | 25 | 15 | 7 | 13 | 1.6 | 0.08 | 0.55 |
| LCS25-025-35-6 | 48 | 130x60x25 | 25 | 20.5 | 8 | 14.5 | 1.6 | 0.08 | 0.55 |
| LCS25-025-55-2 | 24 | 130x60x25 | 25 | 7.4 | 2.9 | 2.5 | 3 | 0.08 | 0.55 |
| LCS25-025-75-2 | 48 | 130x60x25 | 25 | 9.2 | 3.6 | 3 | 3 | 0.08 | 0.55 |
| LCS25-050-15-6 | 24 | 155x60x25 | 50 | 15 | 7 | 13 | 1.6 | 0.08 | 0.616 |
| LCS25-050-35-6 | 48 | 155x60x25 | 50 | 20.5 | 8.8 | 14.5 | 1.6 | 0.08 | 0.616 |
| LCS25-100-15-6 | 24 | 205x60x25 | 100 | 15 | 7 | 13 | 1.6 | 0.08 | 0.808 |
| LCS25-100-35-6 | 48 | 205x60x25 | 100 | 20.5 | 8.8 | 14.5 | 1.6 | 0.08 | 0.808 |
| LCS25-150-15-6 | 24 | 258x60x25 | 150 | 15 | 7 | 13 | 1.6 | 0.08 | * |
| LCS25-150-35-6 | 48 | 258x60x25 | 150 | 20.5 | 8.8 | 14.5 | 1.6 | 0.08 | * |
| LCS25-200-15-6 | 24 | 310x60x25 | 200 | 15 | 7 | 13 | 1.6 | 0.08 | 1.183 |
| LCS25-200-35-6 | 48 | 310x60x25 | 200 | 20.5 | 8.8 | 14.5 | 1.6 | 0.08 | 1.183 |
| LCS50-025-75-1 | 48 | 125x100x50 | 25 | 50 | 20 | 40 | 1.5 | 0.296 | 2.118 |
| LCS50-050-35-6 | 48 | 250x115x50 | 50 | 90 | 20 | 67 | 1.7 | 0.608 | * |
| LCS50-050-75-1 | 48 | 125x100x50 | 50 | 45 | 18 | 30 | 1.6 | 0.33 | 2.57 |
| LCS50-050-75-2 | 48 | 215x100x50 | 50 | 85 | 34 | 30 | 3 | 0.465 | 4.34 |
| LCS50-100-35-6 | 48 | 300x115x50 | 100 | 90 | 36 | 67 | 1.7 | 0.885 | 5.6 |
| LCS50-150-35-6 | 48 | 350x115x50 | 150 | 90 | 36 | 67 | 1.7 | 0.825 | 8 |
| LCS50-250-35-6 | 48 | 450x115x50 | 250 | 90 | 36 | 67 | 1.7 | 0.885 | 14 |


NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. (*)Consult factory



LCS8



LCS25



LCS50

Options & Modifications (Consult factory for availability)

Linear encoder resolutions ----- LCS series: 5µm standard, 1µm optional

Return spring ----- Prevents the shaft from dropping during vertical operation when power is cut.

Increase of force & acceleration ----- 48 volt coil and double coil options are available for some units with 24 volt single coil.

Increase of force accuracy/lifetime -- Low-friction linear guide/extra-long preload linear guide.

SMAC Moving Coil Actuators

The LBS with compact design provides quiet, efficient, and cost effective linear motion.

The SLA incorporates precision cross roller guides with anti-creep protection for increased stiffness and lower friction.



- ✓ Ideal for precision movements/scanning
- ✓ Encoder resolution down to 50 nm with the SLA
- ✓ Compact size

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Maximum Current [Amp] | Moving Mass [kg] | Weight [kg] |
|----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-----------------------|------------------|-------------|
| LBS17-005-52-2 | 24 | 70x35x17 | 5 | 13.5 | 5.4 | 9.6 | 1.4 | 0.028 | 0.22 |
| SLA10-005-55-1 | 24 | 50x50x10 | 5 | 2.2 | (*) | 1.5 | 1.5 | 0.02 | 0.08 |
| SLA10-010-55-1 | 24 | 61x50x10 | 10 | 2.1 | (*) | 1.6 | 1.3 | 0.03 | 0.11 |
| SLA25-010-55-2 | 24 | 72.5x40x25 | 10 | 4 | (*) | 2.7 | 1.5 | 0.05 | 0.203 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. (*)Consult factory



LBS17



SLA10



SLA25

Options & Modifications (Consult factory for availability)

Linear encoder resolutions ----- LBS series: 5µm standard, 1µm optional. SLA series: 5µm standard. 1µm, 0.1µm, and 0.05µm optional.
 Return spring ----- Prevents the shaft from dropping during vertical operation when power is cut.
 Increase of force & acceleration ----- 48 volt coil and double coil options are available for some units with 24 volt single coil.
 Increase of force accuracy/lifetime -- Low-friction linear guide/extra-long preload linear guide.

The LAS series is designed based on the LAL series. Stroke up to 150mm, peak force up to approx. 200N.



- ✓ Soft-Land™ capability and precise force control
- ✓ Ideal for precision positioning and handling fragile material/components

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke [mm] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Max Current [Amp] | Moving Mass [kg] | Weight [kg] |
|-----------------|--------------|------------------|-------------|----------------|----------------------|----------------------|-------------------|------------------|-------------|
| LAS35-025-55-2 | 24 | 135x90x35 | 25 | 31.5 | 12.6 | 15.5 | 2.9 | 0.19 | 1.06 |
| LAS35-025-75-1 | 48 | 150x90x35 | 25 | 18 | 7 | 10 | 1.3 | 0.15 | 0.95 |
| LAS35-050-55-1 | 24 | 135x90x35 | 50 | 10 | 4 | 7 | 1.6 | 0.13 | 1.1 |
| LAS35-050-75-1 | 48 | 135x90x35 | 50 | 12.5 | 5 | 10 | 1.3 | 0.13 | 1.1 |
| LAS35-100-55-1 | 24 | 135x90x35 | 100 | 6 | 2.4 | 3.5 | 1.6 | 0.13 | 1.7 |
| LAS35-100-75-1 | 48 | 135x90x35 | 100 | 7.5 | 3 | 5 | 1.6 | 0.1 | 1.3 |
| LAS55-050-55-1 | 24 | 250x110x55 | 50 | 25 | 10 | 19 | 1.3 | 0.3 | 3 |
| LAS55-050-75-1 | 48 | 250x110x55 | 50 | 40 | 16 | 24.5 | 1.8 | 0.31 | 3 |
| LAS55-100-55-1 | 24 | 250x110x55 | 100 | 16 | 6.4 | 13 | 1.3 | 0.3 | 3.8 |
| LAS55-100-75-1 | 48 | 250x110x55 | 100 | 25 | 10 | 19 | 1.8 | 0.31 | 3.8 |
| LAS55-150-55-1 | 24 | 250x110x55 | 150 | 13 | 5 | 10 | 1.3 | 0.4 | 4.5 |
| LAS55-150-75-1 | 48 | 250x110x55 | 150 | 19.5 | 8 | 13 | 1.8 | 0.31 | 4.58 |
| LAS95-015-75-1 | 48 | 90x70x95 | 15 | 84 | 33 | 53 | 1.7 | 0.25 | 2.1 |
| LAS95-015-75-2 | 48 | 147x95x70 | 15 | 185 | 74 | 58 | 3.2 | 0.5 | 4 |
| LAS95-025-75-2 | 48 | 179x70x95 | 25 | 162 | 65 | 52 | 3.1 | 0.5 | 3.78 |
| LAS95-050-75-1 | 48 | 147x70x95 | 50 | 65 | 26 | 41 | 1.7 | 0.48 | 3.6 |
| LAS300-050-75-2 | 48 | 210x85x120 | 50 | 202 | 80 | 86 | 3 | 0.8 | 8.8 |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list.



LAS35



LAS55



LAS95



LAS300

Options & Modifications (Consult factory for availability)

- Linear encoder resolutions ----- 5µm standard. 1µm and 0.1µm optional for most units. Consult factory for availability.
- Return spring ----- Prevents the shaft from dropping during vertical operation when power is cut.
- Increase of force & acceleration ----- 48 volt coil and double coil options are available for some units with 24 volt single coil.
- Increase of force accuracy/lifetime ----- Low-friction linear guide/extra-long preload linear guide.

SMAC Moving Coil Actuators

The MGR, GRP and LXY have the advantage of independent control of the velocity, acceleration, positioning and force of each axis. This gives you a flexible and accurate tool.



- ✓ Precise force control, measuring and positioning
- ✓ Soft-Land™ capability for sensing product location and dimensions
- ✓ No backlash, no cogging

| Part Number | Voltage [DC] | Size: LxWxH [mm] | Stroke per Axis [mm] | Axis 1 | | | | Axis 2 | | | | Maximum Current [Amp] | Weight [kg] | Maximum Opening |
|----------------|--------------|------------------|----------------------|----------------|----------------------|----------------------|------------------|----------------|----------------------|----------------------|------------------|-----------------------|-------------|-----------------|
| | | | | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Moving Mass [kg] | Peak Force [N] | Continuous Force [N] | Force Constant [N/A] | Moving Mass [kg] | | | |
| MGR7-010-51-1 | 24 | 55x47.5x24 | 5 | 3.8 | (*) | 10.9 | 0.009 | 3.8 | (*) | 10.9 | 0.009 | 0.35 | 0.17 | 10 |
| GRP20-010-51-1 | 24 | 80x90x23 | 5 | 8 | 3.2 | 5.5 | 0.065 | 8 | 3.2 | 5.5 | 0.065 | 1.8 | 0.5 | 10 |
| GRP35-030-55-1 | 24 | 93x110x38 | 15 | 25 | 10 | 17 | 0.1 | 25 | 10 | 17 | 0.1 | 1.5 | 1.5 | 30 |
| GRP35-030-75-1 | 48 | 93x110x38 | 15 | 26 | 10 | 13 | 0.1 | 26 | 10 | 13 | 0.1 | 1.9 | 1.5 | 30 |
| GRP50-030-55-1 | 24 | 90x125x55 | 15 | 35 | 14 | 23 | 0.15 | 35 | 14 | 23 | 0.15 | 1.5 | 2.1 | 30 |
| GRP50-030-75-1 | 48 | 90x125x55 | 15 | 45 | 18 | 23.6 | 0.15 | 45 | 18 | 23.6 | 0.15 | 1.9 | 2.1 | 30 |
| LXY15-015-75-1 | 48 | 111x112x86 | 15 | 22 | 11 | 13 | 0.13 | 25 | 12 | 12 | 0.22 | 2.2 | 1.65 | N/A |
| LXY25-025-75-2 | 48 | 125x125x65 | 25 | 42 | 17 | 14 | 0.19 | 42 | 17 | 14 | 1.5 | 3 | 3.2 | N/A |

NOTE: For any SMAC Moving Coil Actuators, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory. We manufacture actuators to suit our customers' requirements. Please call us if you do not find the right actuator in this list. (*)Consult factory



MGR7



GRP20



GRP35



GRP50



LXY15



LXY25

Options & Modifications (Consult factory for availability)


- Linear encoder resolutions ----- 5µm standard, 1µm and 0.1µm optional for most units. Consult factory for availability.
MGR7: 1µm standard.
GRP20: 1µm standard and 0.1µm optional.
GRP35 and GRP50: 5µm standard, 1µm and 0.1µm optional.
- Increase of force & acceleration ----- 48 volt coil and double coil options are available for some units with 24 volt single coil.
- Increase of force accuracy/lifetime ----- Low-friction linear guide/extra-long preload linear guide.

Multi-Axis Orientation Options


SMAC offers versatile and flexible multi-axis solutions. The systems with SMAC multi-axis solutions deliver the capability to learn and follow a 3D contour or motion path with a high degree of speed, precision, accuracy, and repeatability. All combinations of SMAC actuators can be used: linear, linear slide, linear/rotary and XY stage axis.

SMAC multi-axis solutions feature and utilize linear/circular interpolation and electronic gearing which enables a constant speed while following the chosen XYZ axis contour. Ideal applications are measuring and testing (i.e., quality control), pick and place, deposition, machining, scoring and cutting, to name a few.


Multi-axis systems with SMAC actuators enable total programmability of speed, position and force, all at the same time, with an exceptional degree of accuracy and repeatability. These multi-axis systems offer a wide range of solutions with a number of highly flexible control interfaces. When system integrators consider SMAC actuators, many new opportunities are now available with airless, clean-room capable features. These are some examples of how SMAC actuators have been combined.




Multi-Axis LAL35, LAL95 and LAS95 (3 Axes)



Multi-Axis LXY15 and LAS95 (3 Axes)



Multi-Axis, x2) LXY25 and x1) LAS95 (5 Axes)



Multi-Axis LXY15 and LAL95 (3 Axes)

MCA Inside

MCA (or “Moving Coil Actuator”) Inside is a custom series of actuators built to your size, shape, and form specifications. These actuators would include all the features inherent to SMAC actuators.

MCA Features and Benefits

MCA Inside actuators are based on moving coil actuator technology. They are unique in that force, position, and speed are totally programmable and they provide realtime feedback on the work they are doing while it is being performed. SMAC actuators are designed to perform at exceptionally high speeds or very low speeds and with sub-micron accuracy and repeatability. A patented Soft-Land™ function gives extremely accurate sensing of product location or dimensions.

The features that the SMAC Voice Coil Actuator is known for (such as programmable force, position, and speed, realtime feedback, high speeds, sub-micron accuracy/repeatability, Soft-Land, long life, etc.) can now align with OEM requirements of "dropping into" the form, fit and function of the existing solution. This allows OEMs with an install base or existing designs to utilize SMAC's features to solve problems with minimal inconvenience during the transition.

Advantages with MCA Inside

- Improves speeds, efficiencies, cycle life.
- Eliminates downtime.
- Provides feedback on processes in real time.
- Replaces a ‘problem’ actuator - slow / inflexible / short cycle life - with a Moving Coil Actuator on a currently produced machine.
- Fits into a particular required space on a new machine.
- Allows you to get around the inflexible standard product offerings of many manufacturers.
- Get an actuator that meets the special mechanical requirements demanded for your particular application.

Examples of Custom Models



LBL10 Linear Actuator



LBS17 Linear Slide

VLC Controllers

VLC DC brushed/brushless motor controllers/drivers are designed and manufactured by SMAC. This enables SMAC to offer efficient, competitively-priced solutions with no loss in features or functionality. The product can be adjusted by SMAC to a specific design, or to market or customer needs. SMAC offers a range of single and multi-axis controllers as well as stand-alone amplifiers. Complimentary standard programming software is available. Controllers can also be programmed by mnemonic type command instructions via an RS-232 interface into NVRAM and allows code to be stored in non-volatile RAM, which is then used to enable movements to be made in three different modes. They require no supplementary software. SMAC supports connectivity with a different type of fieldbus systems such as Ethernet/IP, EtherCAT® and CANopen. Please contact us for more information.

| | Part Number | Motor type | Stand-alone | Built-in | Output (Standard) | Digital input | Digital output | Analog input * | Analog output | STO (Safe Torque Off) | Communication interfaces |
|-------------|--------------|-----------------------|-------------|----------|----------------------------|-------------------|-------------------|--------------------|---------------|-----------------------|--------------------------------------|
| Single Axis | VLCI-R3 | brushed/ brushless | | • | 3.5 A cont., 6.5 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 1 Diff | 1 | 2 In, 1 Out | RS232 |
| | VLCI-X1 | | • | | 3.5 A cont., 6.5 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 1 Diff. | 1 S.E. | 2 In, 1 Out | RS232 |
| | VLC-1-07 | | • | | 6 A cont., 7.8 A peak | 8 (opto-isolated) | 8 (opto-isolated) | 2 Diff., 3 S.E. | 3 S.E. | 2 In, 1 Out | Serial (UART) |
| | VLC-1-13 | | • | | 10 A cont., 13 A peak | 8 (opto-isolated) | 8 (opto-isolated) | 2 Diff., 3 S.E. | 3 S.E. | 2 In, 1 Out | Serial (UART) |
| | VLC-ETC | | • | | 3.5 A cont., 6.5 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 1 Diff. | 1 S.E. | 2 In, 1 Out | Serial (UART), EtherCAT (2-ports) |
| | VLCI-CAN-07 | | • | | 3.5 A cont., 6.5 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 1 Diff. | n/a | 2 In, 1 Out | RS232, CAN |
| Dual Axis | VLC-25-07 | brushed/ brushless | • | | 6 A cont., 7.8 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 2 Diff., 3 S.E. | 2 S.E. | 2 In, 1 Out | RS232 |
| | VLC-25-13 | | • | | 10 A cont., 13 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 2 Diff., 3 S.E. | 2 S.E. | 2 In, 1 Out | RS232 |
| | VLC-2-EIP-07 | | • | | 6 A cont., 7.8 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 2 Diff., 3 S.E. | 2 S.E. | 2 In, 1 Out | RS232, Ethernet/IP |
| | VLC-2-EIP-13 | | • | | 10 A cont., 13 A peak | 4 (opto-isolated) | 4 (opto-isolated) | 2 Diff., 3 S.E. | 2 S.E. | 2 In, 1 Out | RS232, Ethernet/IP |

* Diff. = Differential and S.E. = Single-Ended



VLCI-R3



VLCI-X1



VLC-1-07 / VLC-1-13



VLC-ETC



VLCI-CAN-07




VLC-25-07 / VLC-25-13



VLC-2-EIP-07/ VLC-2-EIP-13

SMAC Moving Coil Actuators



Why Use SMAC Cables?

SMAC actuators are used in numerous high speed, high cycle applications and are guaranteed for millions of cycles. For this reason, it is imperative that the cables used to connect with our actuators are capable of similar arduous duty cycles and life span. Only cables manufactured by SMAC can be guaranteed to meet the rigorous standards required during use. Many years of experience has taught us that cheaper third party cables simply are not up to the task required. They are, in fact, one the most common causes of technical problems experienced by our customers.

| | Single Axis Controller | | | | | Dual Axis Controller | |
|--|---|---------|-------------|--------------------------------------|---------------|----------------------|-----------------|
| Actuator | Stand Alone | | | | Built-in | Stand Alone | |
| Models | VLCI-X1 | VLC-ETC | VLCI-CAN-07 | VLC-1-07/13 | VLCI-R3 | VLC-25-07/13 | VLC-2 EIP-07/13 |
| CBL* / CTL* | VAH-6LOD26-03 | | | VAH-4LOD26-03 | | | |
| 2x CBL* / CTL* | | | | | VAH-4LTD26-03 | | |
| LBL / LDL | MAH-6LOD26-03 | | | MAH-4LOD26-03 | | | |
| LDL Built-in Controller Type | | | | MAH-VCI2626-02 | | | |
| LBR | MAH-6RED026-03 | | | MAH-4RED026-03 | | MAH-4RTD026-03 | |
| LCA(S)* / LCB / MLA (single-pole/brushless) | VAH-6LOD26-03 | | | VAH-4LOD26-03 | | | |
| LCA (S)* (Multi-pole/brushless) | MAH-6LOD26-03 | | | MAH-4LOD26-03 | | | |
| 2x LCA(S)* / LCB / MLA | | | | | VAH-4LTD26-03 | | |
| 2x LBL* / LCA (S)* (Multi-pole/brushless) | | | | | | MAH-4LTD026-03 | |
| SLA10/ SLA25* | VAH-6LOD26-03 (SLA10 requires LAH-PT12-26 cable) | | | VAH-4LOD26-03 | | | |
| LAL35/LAL95 | VAH-6LOD26-03 | | | VAH-4LOD26-03 | | | |
| LAL55/LAL300/LAL500 | VAH-6LOD-03 | | | VAH-4LOD-03 | | | |
| 2x LAL35/LAL95 | | | | | | VAH-4LTD26-03 | |
| 2x LAL55/LAL300/LAL500 | | | | | VAH-4LTD-03 | | |
| LAR35 | VAH-6RED26-03 (with 2x controllers) | | | VAH-4RED26-03 (with 2x controllers) | | VAH-4RTD26-03 | |
| LAR31-030 | MAH-6RED226-03 (with 2x controllers) | | | MAH-4RED226-03 (with 2x controllers) | | MAH-4RTD226-03 | |
| LAR31-050 / LAR51-058 | MAH-6RED026-03 (with 2x controllers) | | | MAH-4RED026-03 (with 2x controllers) | | MAH-4RTD026-03 | |
| LAR55/LAR95/LAR300 | VAH-6RED-03 (with 2x controllers) | | | VAH-4RED-03 (with 2x controllers) | | VAH-4RTD-03 | |
| LCR13/LCR16/LCR20 Under 25mm stroke | MAH-6RED226-03 (with 2x controllers) | | | MAH-4RED226-03 (with 2x controllers) | | MAH-4RTD226-03 | |
| LCR13/LCR16/LCR20 35mm stroke and above | MAH-6RED026-03 (with 2x controllers) | | | MAH-4RED026-03 (with 2x controllers) | | MAH-4RTD026-03 | |
| MGR | VAH-6RED26-03 (with 2x controllers) | | | CAH-4RED26-03 (with 2x controllers) | | VAH-4RTD26-03 | |
| GRP20/GRP35/GRP50*** | VAH-6RED26-03 (with 2x controllers) | | | VAH-4RED26-03 (with 2x controllers) | | VAH-4RTD26-03 | |
| LXY15/LXY25 | GRP-6RED26-03 (with 2x controllers) | | | GRP-4RED26-03 (with 2x controllers) | | GRP-4RTD26-03 | |

* No cable required for flying lead option. *** Old type of GRP50 requires LAH-GRP26-03 cable.

Options & Modifications (Consult factory for availability)

Cable length ----- 3m standard, optional 10m length is available. Consult factory for other length.

Superflex ----- Suitable for robotic applications.

Non-SMAC controller connector ----- Consult factory for details.

SMAC Moving Coil Actuators


Graphical User Interface (GUI)

SMAC Graphical User Interface provides a simple and straightforward way to quickly configure motion parameters of a variety of SMAC single/dual axis actuators and controllers. Pre-installed, user configurable application-based GUIs are also available.

- Little to no programming experience required
- Menu-driven, Windows based, easy setup
- Pre-programmed with application-specific features
- Real time analysis
- Data and graphical feedback tools
- Built-in tutorial and help features


LCC Control Center

Achieve high level programming with no programming experience, monitoring and logging of parameters, fine-tuning of control parameters for LCC and CBC controller.



LAC-X Editor

Easy setup and tuning of control parameters for LAC-1 and LAC-25.



Thread Check Center: TCC

User configurable Thread-Checking applications. Fully automated 100% inspection of internal & external threads. Verification of counter bore height, thread pitch, oversized/undersized threads, cross thread and shallow thread, etc.



Capping Control Center: CCC

User configurable threaded bottle/container capping applications. Detect and report no/obstructed cap. Adjust force and torque, show the different quality check capabilities such as cap height, torque limit, force required to press-in, and even check the clicks on child proof caps.




Gauging Control Center: GCC

User configurable gauging applications. Provide real time plot of measured values in relation to limits. The user may save a .csv or image file of the measured values or graph area respectively for data logging.



Ejection Control Center: ECC

User configurable Ejection applications. Select and program between 4 types of ejection sequence including soft eject, rapid eject etc. Control velocity for ejection based on customer cycle time requirements. Adjust force to eject based on the weight/mass of the object to eject. Manipulate position to park the actuator based on the program sequence.




Leak Test Center: LTC


User configurable Leak testing applications: Select and program between two types of leak testing procedure(Velocity and Force). Unique capability of SMAC actuator to soft land on the object and applying force can be programmed using this GUI. Precise monitoring of displacement of the bottle/container/ or any testing sample during leak testing. Adjust the force to be applied on the test object using this software.




Configuration with SMAC Controllers



Configuration with Non-SMAC Controllers




Configuration for Flying Lead Cable




CAL, CBL, CTL, LCA, LCB, LBL, MGR and SLA series

Configuration for Pigtail Cable




Configuration for SMAC Cable




LAL(S), LAR, GRP and LXY series

Configuration with 2 Single Axis Controllers



LAR and LCR series

Configuration with 1 Dual Axis Controller



LAL(S) series

SMAC Moving Coil Actuators

INSTALLATION GUIDE

Duty Cycle

For any SMAC Moving Coil Actuator, the maximum recommended continuous duty current is 600mA supplied to the actuator over a 1 second period. For anything beyond this in terms of current draw or time please consult the factory.

NOTE: Failure to observe this duty cycle recommendation may result in the actuator sustaining damage through overloading. Overloading will overheat the coil and may cause deformation or an impact on the magnet housing.

Continuous Force

Peak force applied for duration shorter than 0.4 sec. in one second interval. (force mode): 40% of peak force, continuous.

Force Mode

The specified current may be applied continuously to generate the desired force. However, the recommended continuous force limit should be set in the control program.

In vertical operation, the actuator rod will drop when power is cut off. The rod in a lowered position may be damaged by other moving parts in the machine. A return spring (optional feature) will keep the rod raised. A safety lock-out should be installed in the machine program to confirm the rod location before another interfering component can be moved.

SMAC actuators are equipped with these safety features:

- Index line/home position: used to monitor absolute position
- Breakaway shaft (optional)

Safety Considerations

Unintentional full force may be applied continuously under the following conditions:

- missed target position
- excessive friction
- equipment malfunction, i.e. jam

If left undetected, this can cause destruction of the coil in some units. A servo program should perform the following checks regularly:

- Re-home: to assure target position has not shifted beyond end of stroke
- Time-outs: to shut power down within 10 seconds of error detection
- Following Error Limits: software safety

Mounting

If the actuator is mounted vertically, the shaft drops down when the actuator is powerless. It is possible that other moving parts of the machine may damage the actuator at this position. A return spring would hold the actuator in an upper position when it is powerless.

A safety function in your machine should check the actuator's current position before other components may move into the working area of the actuator.

INDIVIDUAL MODIFICATION

Many of our standard actuators listed on previous pages are compatible with both add-on options and modifications. In addition to the standard vacuum and spring option SMAC can offer the following modifications subject to approval by the factory.

Linear Guide Options

Increased rigidity and side load tolerance can be gained by using a higher specification "wide guide". Additionally, in force sensitive applications we can fit a low friction guide.

Double Coil

Integrating an extra coil can enhance both force and acceleration.

Custom Nose-Bushing

An extended nose bushing with increased side load tolerance are available on many models. We can also offer scraper and wiper seals around the shaft to protect the bearings from excessive wear in harsh environments.

Custom Shafts

In addition to the standard male/female rod ends we can also offer options such as "breakaway" shafts and custom shaft diameters.

10µm T.I.R.

Total indicator run-out under 10µm is available on several linear/rotary models.

Rotary

Increased torque/gear ratio can be gained by using alternative geared motors or direct drive motors.

Higher rotary encoder resolutions are optional. Please consult factory for availability.

If a longer life rotary is required, then we can fit a brushless rotary motor.

Flying Lead

Instead of the standard chassis connector we can offer a flying lead option. The flying lead is standard for all the CA and LCA series actuators.



Cable Options

Whenever an SMAC actuator is mounted to any 3rd party device such as a gantry or multi-axis robot, SMAC strongly recommends that a superflex cable is used. Cable lengths with a standard of 3 meters up to a maximum of 10 meters can be offered.

Optical Encoders

SMAC encoders are made using optical components provided by large volume manufacturers of printers, cameras, cell phones and independent manufacturers of standard mixed signal ASIC semiconductor products used in optical encoders around the world.

We use these high reliability optical components that are made in the millions per year to take advantage of the latest manufacturing technologies used in these fields and the latest design features patented by these suppliers. Technologies include using Interlaced Photo Detector Arrays to better balance the light viewed across the photo sensor array and average imperfections in the code pattern of the scale, LED light intensity auto gain to compensate for LED aging and temperature changes and GUI control of the many features selected in the interpolator and signal conditioning ASIC.

SMAC Advantages

- Reflective and diffractive type encoders allow smaller cross-sections with all components on one side of the scale
- Interlaced optical ASIC's allow reader head mounting tolerance rotation of ± 0.2 MM and gap settings of 0.5 to 1.0 MM for easier installation.
- Small size ASIC's allow PCB sizes down to 6 MM wide for tighter fits.
- Integrated Optical ASIC interpolators to 16x for 5 Micron linear encoders and 24,000 cpr, 12 MM diameter rotary encoders.
- 20 Micron pitch Diffractive encoder modules with GUI calibrated ASIC interpolation for resolutions down to 50 Nanometers.
- Very compact. Custom packaging available for OEM
- Cost competitive
- Factory calibrated. User programming available for in field optimization.

Custom Encoders

SMAC will work with you to build custom encoders that fits your project specifications. Please contact us if you don't find that any of our standard products will fill your needs.



LL Series Linear Encoder

The LL linear encoder is a miniature non-contacting high resolution incremental linear encoder, which delivers two count channels in quadrature RS422 output signals. This series is available in 1 and 5 micron resolution.

Features

- Light Source: Light Emitting Diode;
- Light Sensor: Optical ASIC
- Resolution after quadrature: 5 and 1 micron
- Output Format: Differential RS422 line driver output. Two count channels A and B in quadrature with an optional ZR output;
- Quadrature spec.: $90^\circ \pm 45^\circ$ at maximum conditions;
- Rise and Fall Time: 1 μ s max., with 1000 pF load;
- Travel length: up to 250mm (special lengths available on request)



SLE-LI Series Linear Encoder

The SLE-LI encoder is a miniature non-contacting high resolution Incremental linear encoder, which delivers two count channels in quadrature RS422 output signals. This series is available in 1, 0.5, and 0.1 micron resolution. 150mm scale length standard.

Features

- Light Source: Light Emitting Diode;
- Light Sensor: AEDR Optical ASIC;
- Resolution after quadrature:
- Output Format: Differential RS422 line driver output. Two count channels A and B in quadrature with an optional ZR output;
- Quadrature spec.: $90^\circ \pm 22^\circ$ at maximum conditions;
- Rise and Fall Time: 1 μ s max. into 1000 pF load;
- Travel length: up to 264 mm.



SLE-35 Series Linear Encoder

The SLE-35, high resolution linear encoder is similar in mounting to other industry standard enclosed linear encoders. This model is a miniature non-contacting high resolution incremental linear encoder, which delivers two count channels in quadrature (called A and B) as output signals. The two output waveforms are 90 degrees out of phase and indicate both the position and the movement direction: when Channel A leads Channel B, for example, then the movement is from left to right of the scale when viewing the pattern side of the scale. Otherwise, if B leads A, then the displacement is in the opposite direction. This encoder is available in 0.1 and 0.05 micron resolution.

Features

- Light Source: Light Emitting Diode;
- Light Sensor: AEDR Optical ASIC;
- Resolution after quadrature: 0.1 μ m or 0.05 μ m
- Output Format: Differential RS422 line driver output. Two count channels A and B in quadrature with an optional ZR output;
- Quadrature spec.: $90^\circ \pm 45^\circ$ at maximum conditions;
- Rise and Fall Time: 1 μ s max. into 1000 pF load;
- Travel length: up to 150 mm standard. Please contact us for information about longer lengths.



SRE-30 Series Rotary Encoder

The SRE-30 series, high resolution rotary encoder is similar in mounting to other industry standard enclosed rotary encoders. This model is a miniature non-contacting high-resolution incremental rotary encoder, which delivers two count channels in quadrature (called A and B) as output signals. The two output waveforms are 90 degrees out of phase and indicate both the position and the movement direction: when Channel A leads Channel B, for example, then the movement of the disc is clockwise. Otherwise, if B leads A, then the displacement is in the opposite direction. This encoder is available in 1000, 2000, 4000, 8000 and 16000 CPR resolution.

Features

- Light Source: Light Emitting Diode;
- Light Sensor: Optical ASIC;
- Resolution: 1000, 2000, 4000, 8000 or 16000 CPR
- Output Format: Differential RS422 line driver output. Two count channels A and B in quadrature with an optional ZR output;
- Quadrature spec.: $90^\circ \pm 45^\circ$ at maximum conditions;
- Rise and Fall Time: 1 μ s max. into 1000 pF load;
- 6mm standard shaft size

High Torque Brushless 3-Phase DC Motor

The HT is a new revolutionary high torque brushless DC motor. Compared to other brushless motors, the HT Motor has a flat torque-speed curve meaning that the speed is less influenced when the torque is increased. The secret to that is found how the magnetic circuit is built. A combination of SMAC's patent pending Halbach magnets and printed coil technology achieves higher torque/amp. Most small motors run at high RPMs but have low torque. These are not well fitted for robotic applications. Expensive and heavy gears are required to get to the required torque. Higher currents and/or voltages are needed to get useful torques.

| Part Number | Dimension [mm] | Apply Voltage [VDC] | Power [W] | Terminal Resistance (phase to phase) [Ohm] | Efficiency, maximum [%] | No-load speed [RPM] | No-load current [A] | Stall torque [mNm] | Stall current [A] | Motor type | Pole pair | Rotor mass [gr] | Total mass [gr] | Encoder Option | Gearbox Option |
|-------------|----------------|---------------------|-----------|--|-------------------------|---------------------|---------------------|--------------------|-------------------|------------|-----------|-----------------|-----------------|----------------|----------------|
| HT35 | Ø35x75 | 48 | 26 | 13.4 | 72.7 | 2388 | 0.08 | 497 | 3.5 | Brush-less | 6 | 146 | 256 | 2K or 24K | 4:1 or 16:2 |
| HT55 | Ø53x80 | 48 | 37.8 | 8.3 | 85 | 851 | 0.36 | 1995 | 6.1 | Brush-less | 6 | 350 | 980 | 2K or 24K | 4:1 or 16:1 |

NOTE: We will work with you to build custom motor that fits your project specifications. Please contact us if you don't find that any of our standard products will fill your needs.



HT35



HT55

SMAC Advantages

- Halbach magnet circuits that increase torque > 2 times due to flux density of over 10K gauss.
- SMAC's patent pending printed coil technology that allows for winding configurations not possible using conventional mechanical winding methods.
- Reduces new motor tooling costs to a fraction of the old conventional methods.

Select Your Actuator

In order to select the correct actuator for your application, the following parameters should be known.

| | |
|--|--|
| Machine Function: | Mount Details: |
| Space Available [mm]: x= y= z= | Mount surface: Axis side surface / Actuator side surface |
| Orientation: Horizontal / Vertical rod down / Vertical rod up | Environment: Debris / Dust / Vapor / Temperature / Harsh Cleaning Chemicals |

| Specifications | |
|---|------------------------|
| Linear | Rotary |
| Stroke [mm]: | Degree of Rotation: |
| Max. Velocity: | Max. Rot. Velocity: |
| Min. Velocity: | Min. Rot. Velocity: |
| Max. Acceleration: | Max. Rot Acceleration: |
| Max Force [N]: Continuous force [N]: | Max Torque: |
| Force Resolution [N]: | Torque Resolution: |
| Force Repeatability [N]: | Torque Repeatability: |
| Encoder Resolution [μm]: 5 / 1 / 0.1 / other () | Encoder Resolution: |
| Repeatability [μm]: | Repeatability: |
| Cycles/sec: | Cycles/sec: |
| Expected Cycle Life: | Expected Cycle Life: |

| Rod | | |
|--------------------------|---------------------------------|--|
| Moving part: Rod / Slide | Rod Length (Full Retract) [mm]: | Tip: Male / Female / Blank / Custom |
| Material requirement: | Vacuum through shaft: Yes / No | Thread of shaft: Standard / M () |


| Special Features | | | |
|---------------------------|----------------------|-------------------------------|----------------------|
| Plating: | Cable: | Spring: | Linear Guide: |
| Standard / Black anodized | Standard / Superflex | Full return / Counter balance | Standard / Long life |

| Controller or Amplifier | | | |
|-----------------------------------|------------------------|----------------------|---------------|
| Location: | Cable: | I/O: | Smart Driver: |
| Built-in / External at () m | Standard / Flying lead | Number and TTL / 24V | Yes / No |

| Payload | | |
|----------------|---|----------|
| Weight [gram]: | Size: (LxWxH) | Inertia: |
| Shape: | Relation to rod/slide: Fixed / Push only / Other | Remarks: |

APPLICATIONS

Mechatronic SMAC electronic actuators are used widely in automotive, packaging, electronics, robotics, pharmaceutical, medical assembly, laser cutting, high speed scanning, glass cutting, dispensing, switch testing, spot welding, soldering, and measuring applications to name but a few. SMAC is constantly working on new and diverse applications with both OEMs and end-users across the world.



Pick & Place




The precision Z-theta motion within one small actuator, providing a convenient pick, orient and place. The unique Soft-Land function allows the unit to gently land on a delicate component with a controlled force, avoiding damage to the component. These characteristics make SMAC electric actuators ideal for assembling small, fragile components.



Switch Testing



In-line durability test. Measuring click point, force and displacement. Report force vs. position with SPC data collection. Life testing of components as well as measurement and QA reporting functions in one unit.



Touch Screen Testing




Quality check for touch screen, including zoom in and out, swiping motion, touch screen fatigue test. SMAC's Soft-Land procedure, programmable force, high speed and detailed feedback are essential in the testing.



100% Automated Thread Check




Fully automated 100% inspection and test of screw thread check for optimal quality assurance. The unique low-cost SMAC solution enables you to automatically check the following screw thread parameters: Oversize/undersized threads, cross threads, thread depth, no-threads, mis-located threads, thread pitch, and shallow/blocked hole.



Measuring, Bore Gauging and Groove Inspection



100% measure and test inline production of small components for quality control. The SMAC actuator conducts multiple point gauging on parts externally and internally within a few seconds. It can run 24/7 and enables 100% data feedback and verification of each individual test on each individual part.



SMAC Moving Coil Actuators

Tensioning with Precision Force Control



SMAC excels at force control which is key for tensioning materials such as car batteries. Force resolution of 10 grams maintained over the entire force range. Easily replaces low friction pneumatic cylinders that have inconsistent force throughput. Response time 10x better than our closest competitor.



Dispensing / Filling



SMAC actuators' repeatable positioning coupled with high speed allows you to more precisely and repeatedly control the dosing amount. SMAC actuators also allow for easy change over for different dosing requirements based upon the material and container size.



High Speed Pressure/Leak Detecting



SMAC actuator senses the surface of container/package, push with specific force and monitor the movement to determine pressure in container/package. This solution can be used for soft pouch packaging such as contact lens or single-served coffee "pods."



Rejecting, Diverting, and Multi-Lane Sorting



SMAC can reject or divert one container at line speeds over 1200 containers/ minute. Movement of container is smooth, fast, and gentle with unique Soft-Land™ feature. Container will not tip over because of force and velocity control.



Capping



SMAC linear rotary actuator rotates the cap while pushing down. Actuators can press with programmable force and provide torque feedback that informs when the cap has torqued out (or not) to ensure a quality operation. It shows the different quality check capabilities such as cap height, torque limit, force required to press in, and even check the clicks on child proof caps.



Assembly



Assembly requires both precise placement and precise low force control. SMAC linear rotary actuators perform pick, orient, and place movements in a single unit. Precise force control and Soft-Land™ capability preventing parts damage delivers a great advantage. Feedback of assembly positioning provides real time quality control information.



Smart Screwdriver



SMAC linear rotary actuators are an all in one solution. Fast approach, then find the surface with Soft-Land™ capability. Turn counter clock-wise, screw moves up, then drops as first thread found, then start rotating clock-wise. First a “snug” torque is applied, when there are a number of screws holding a part on the clamping surface, then a final torque is applied. Monitoring the torque and pitch verification. Good, shallow, cross/no-threads, and the precision of the thread are detected through linear position feedback.



High Speed On-the-Fly Labeling



The label applicator (SMAC actuator) matches the speed of the conveyor as the product comes through. High cycle rate, energy efficient, and adjustable speed and height for the different kind of products. The Soft-Land™ capability allows the actuator to apply labels with controlled low force.

Scanning



A series of precise short movements with repeatability in micron or sub micron ranges used for moving lenses/cameras, wafer scanning, microscopy, cytometry, etc. SMAC actuators eliminate incremental errors that come with the use of open-loop actuators. SMAC's precision actuators are fully close-looped and provide extremely accurate position data and positioning capability with resolution as to five nanometers. Easy setup, compact, all-in-one package is ideal for integration to existing equipment and new developments.



Material Test




SMAC actuators can be programmed to develop a motion profile required. By measuring the force used to stretch/manipulate the material to the prescribed length, the gradual degradation of the material could be continuously monitored.

Glass Cutting / Scoring



Precision work in grinding, cutting, and polishing processes can be easily done by SMAC programmable actuator. Precise force control and the ability to track a surface with constant force throughout the stroke are important when handling brittle material. SMAC's unique Soft-Land function, the ability to apply as low force as 0.1N or less, and move with a set force while bevelling or cutting is something SMAC can easily do.



SMAC Moving Coil Actuators

The SMAC 12 Month Product Guarantee

SMAC Corporation designs and manufactures advanced electric actuators. All SMAC actuators are quality products specifically designed and built for long service. Therefore, all actuators appearing in this catalog are guaranteed for a period of twelve months from the original date of shipment from our factory.

The guarantee conditions are effective when a SMAC actuator is connected via a SMAC or SMAC approved cable/connector and controlled by either a SMAC or SMAC approved controller. If a customer wishes to use a cable/connector or controller which is neither manufactured by, nor qualified/approved by SMAC, SMAC offers a test and qualification service to the customer. Once tested and approved the standard SMAC guarantee applies. Please contact your local SMAC branch for details. This guarantee is limited to a one-time replacement or rebuilding of any actuator which should fail to operate properly.

Actuators must be returned with transportation prepaid and received at our factory within the guarantee period. They will be returned to the customer at the expense of SMAC.

No claims for labor, material, time, damage or transportation are allowable. Actuators damaged as a result of misapplication by the customer are excluded from this guarantee. The guarantee does not apply to loss or damage caused by fire, theft, riot, explosion, labor dispute, act of God or other causes beyond the control of SMAC. SMAC shall in no event be liable for remote, special or consequential damages, under the SMAC guarantee or under any implied warranty.

The above guarantee is our manner of extending the engineering and service resources of the SMAC organization to assure our customers long and continued satisfaction.

The SMAC Rebuild Program

Actuators no longer covered by the SMAC guarantee can be rebuilt under the SMAC rebuild program. Our continued research and development program extends the life of our actuators making them even more reliable under adverse operating conditions. Actuators returned under this program are completely disassembled, inspected and rebuilt to current operating standards wherever possible, tested and returned within a few days for a reasonable charge (typically 35% of standard list price). For 90 days from date of shipment from our factory, all rebuilt actuators carry the same guarantee as provided for new actuators.

SMAC products have been tested and found to be fully compliant with EN 50082-2 & EN 55011 Group 1, Class A.

Terms & Conditions of Sale

SMAC manufactures and sells actuators, controllers and cables. It has a standard warranty policy covering these products. SMAC does not offer integration services. These are the responsibility of SMAC distribution and their customers. This means SMAC takes no responsibility for software programming, mechanical designs and all other engineering involved in a project using SMAC devices. SMAC may, at its discretion, offer technical recommendations or suggestions to help its customer, the distributor, on a particular application. SMAC will only do this once a signed release of responsibility is received from its customer.

U.S. and world wide patents issued & applied for. SMAC improves its product line on a continuing basis. Specifications and mechanical dimensions are subject to change without notice. Please consult factory before proceeding with your design.

SMAC

Moving Coil Actuators

AVS Danmark ApS • Skelvej 18 • 2640 Hedehusene • +45 46 56 43 43 • www.avsdanmark.dk